

HydAway Test Report Summary



HYDAWAY HYDRAULICS, INC. MOCK-UP TEST REPORT

SCOPE OF WORK
PERFORMANCE TESTING ON AN OPERABLE DOOR SYSTEM

REPORT NUMBER
R9063.01-120-32 R0

TEST DATES
11/18/24 - 12/18/24

ISSUE DATE
01/13/25

RECORD RETENTION END DATE
12/18/28

PAGES
43

DOCUMENT CONTROL NUMBER
RT-R-AMER-Test-2744 (10/11/21)
© 2017 INTERTEK





Total Quality. Assured.

130 Derry Court
York, Pennsylvania 17406

Telephone: 717-764-7700
Facsimile: 717-764-4129
www.intertek.com/building

TEST REPORT FOR HYDAWAY HYDRAULICS, INC.

Report No.: R9063.01-120-32 R0

Date: 01/13/25


**REPORT ISSUED TO
HYDAWAY HYDRAULICS, INC.**

305 4th Street
Suite B
Brookings, SD 57006

**PROJECT
10' X 10' DOOR**



For INTERTEK B&C:

COMPLETED BY:	Joe W. Enriquez
TITLE:	Technician – Project Testing
SIGNATURE:	 <small>Digitally signed by Joe Enriquez</small>
DATE:	01/13/25

REVIEWED BY:	Thomas E. Lawlor
TITLE:	Manager – Project Testing
SIGNATURE:	
DATE:	01/13/25

JWE:rdw

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST METHODS

Mock-up testing was performed in accordance with referenced test methods as specified in the bid documents.

Air Infiltration: ASTM E283/E283M-19, *Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Skylights, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen*. Testing was conducted at 1.57 and 6.24 psf positive static air pressure differences.

Static Pressure Water Resistance: ASTM E331-00(2023), *Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference*. Testing was conducted at 8.0 and 15.0 psf positive static air pressure differences for 15-minute durations. Water was applied to the mock-up at a minimum rate of 5 gal/ft²/hr.

Structural Performance: ASTM E330/E330M-14(2021), *Standard Test Method for Structural Performance of Exterior Windows, Door, Skylights and Curtain Walls by Uniform Static Air Pressure Difference*. Testing was conducted at positive and negative loads as described in the test procedure and listed in the test results.

GENERAL MOCK-UP DESCRIPTION

Project Type

The mock-up was comprised of a steel-framed hydraulic-powered operable door with exterior glazing.

Mock-Up Size

Door: 10' 0" wide by 10' 0" high

Material Source/Installation

The mock-up materials/components were supplied and installed by representatives from Hydaway Hydraulics, Inc.



Total Quality. Assured.

130 Derry Court
York, Pennsylvania 17406

Telephone: 717-764-7700
Facsimile: 717-764-4129
www.intertek.com/building

TEST REPORT FOR HYDAWAY HYDRAULICS, INC.

Report No.: R9063.01-120-32 R0

Date: 01/13/25

FINAL TEST RESULTS (Continued)

DATE:	December 18, 2024	TEMP:	43°F	BP:	29.72 inHg
TITLE OF TEST		MEASURED		ALLOWED	
Preload @ +25.0 psf		---		---	
Static Pressure Air Infiltration @ 1.57 psf		PASSED			
Operable Door		0.10 cfm/ft ²		0.10 cfm/ft ² max	
Static Pressure Air Infiltration @ 6.24 psf		N/A			
Operable Door		0.21 cfm/ft ²		For information only	
<i>General Note: All parties agreed to separately evaluate the glass/glazing from the fixed and operable frames during the remaining static water penetration tests.</i>					
Static Pressure Water Resistance @ 8.0 psf – Fixed & Operable Frames		PASSED			
		No uncontrolled leakage		No uncontrolled leakage	
Uniform Load Deflection		PASSED			
@ +25.0 psf (Preload)		No visible damage		No visible damage	
@ +50.0 psf (Design Load)		Condition mock-up only, no readings		Condition mock-up, no readings	
@ -25.0 psf (Preload)					
@ -50.0 psf (Design Load)					



Total Quality. Assured.

130 Derry Court
York, Pennsylvania 17406

Telephone: 717-764-7700
Facsimile: 717-764-4129
www.intertek.com/building

TEST REPORT FOR HYDAWAY HYDRAULICS, INC.

Report No.: R9063.01-120-32 R0

Date: 01/13/25

FINAL TEST RESULTS (Continued)

DATE:	December 18, 2024	TEMP:	43°F	BP:	29.72 inHg
TITLE OF TEST		MEASURED		ALLOWED	
Repeat Static Pressure Air Infiltration @ 1.57 psf		PASSED			
Operable Door		0.10 cfm/ft ²		0.10 cfm/ft ² max	
Repeat Static Pressure Air Infiltration @ 6.24 psf		N/A			
Operable Door		0.21 cfm/ft ²		For information only	
Uniform Structural Overloads		PASSED			
@ +37.5 psf (Preload)		No visible damage See Table #2 and Sketch #2		No structural failure See Table #2 and Sketch #2	
@ +75.0 psf (Overload)					
@ -37.5 psf (Preload)					
@ -75.0 psf (Overload)					

SECTION 6

CONCLUSION

Regarding the glass tested, no conclusions of any kind regarding the adequacy or inadequacy of the glass in the test specimen are to be drawn from the test. Tape or film, or both, were not used to seal against air leakage; this did not influence the results of the testing.


TEST REPORT FOR HYDAWAY HYDRAULICS, INC.

Report No.: R9063.01-120-32 R0

Date: 01/13/25

SECTION 8
SKETCHES

Interior
View



PROJECT NO.
R9063.01

PROJECT NAME: 10' X 10' Door
CLIENT: HydAway Hydraulics, Inc.



Total Quality. Assured.

130 Derry Court
York, Pennsylvania 17406

Telephone: 717-764-7700
Facsimile: 717-764-4129
www.intertek.com/building

TEST REPORT FOR HYDAWAY HYDRAULICS, INC.

Report No.: R9063.01-120-32 R0

Date: 01/13/25

SECTION 9 TABLES

TABLE #1 - Uniform Load Deflection (Deflection in inches)

INDICATOR LOCATION	POSITIVE +50.0 psf	NET DEFLECTION	NEGATIVE -50.0 psf	NET DEFLECTION	ALLOWED*
1	0.090		0.210		
2	0.380	0.085	0.390	0.110	0.314
3	0.500		0.350		
4	0.150		0.200		
5	0.550	0.250	0.400	0.075	0.628
6	0.450		0.450		
7	0.550		0.350		
8	0.410	0.045	0.350	0.085	0.314
9	0.180		0.180		

*General Note: Allowable amounts are based on $L/175$ of their clear span for framing members. Refer to Sketch #2 for dial indicator locations and to the test procedure for additional information regarding allowable deflections.

TABLE #2 - Uniform Structural Overloads (Permanent Set in inches)

INDICATOR LOCATION	POSITIVE +75.0 psf	NET PERM. SET	NEGATIVE -75.0 psf	NET PERM. SET	ALLOWED*
1	0.000		0.010		
2	0.005	0.000	0.010	0.000	0.110
3	0.010		0.010		
4	0.000		0.000		
5	0.010	0.005	0.010	0.005	0.220
6	0.010		0.010		
7	0.010		0.010		
8	0.000	-0.005	0.010	0.000	0.110
9	0.000		0.010		

*General Note: Allowable amounts are based on 0.2% of their clear span for framing members. Refer to Sketch #2 for dial indicator locations and to the test procedure for additional information regarding allowable deflections.

TEST REPORT FOR HYDAWAY HYDRAULICS, INC.

Report No.: R9063.01-120-32 R0

Date: 01/13/25

SECTION 10
PHOTOGRAPHS



Photo No. 1
Exterior View During Static Air
Infiltration Testing @ 1.57 psf & 6.24 psf



Photo No. 2
Exterior View During Static Water
Penetration Testing @ 8.0 psf

TEST REPORT FOR HYDAWAY HYDRAULICS, INC.

Report No.: R9063.01-120-32 R0

Date: 01/13/25




Photo No. 17

**Interior View of New Gasket Material Applied to
Inner Face of Operable Steel Frame (Two Rows at Jambs)**



Photo No. 18

**Interior View of New Gasket Material Applied to
Inner Face of Operable Steel Frame (Two Rows at Jambs)**

TEST REPORT FOR HYDAWAY HYDRAULICS, INC.

Report No.: R9063.01-120-32 R0

Date: 01/13/25



Photo No. 19
Exterior View of Operable Steel Frame at Sill with New Horizontal Gasket and Aluminum Angle




Photo No. 20
Exterior View of Sealant Applied to Glazing Trim Joinery



Total Quality. Assured.

TEST REPORT FOR HYDAWAY HYDRAULICS, INC.

Report No.: R9063.01-120-32 R0

Date: 01/13/25

130 Derry Court
York, Pennsylvania 17406

Telephone: 717-764-7700

Facsimile: 717-764-4129

www.intertek.com/building



Photo No. 25

**Interior View of Threshold Installed and Sealed at
Sill of Fixed Steel Frame**



Photo No. 27

**Interior View of Threshold Installed and Sealed at
Sill of Fixed Steel Frame**



Total Quality. Assured.

130 Derry Court
York, Pennsylvania 17406

Telephone: 717-764-7700

Facsimile: 717-764-4129

www.intertek.com/building

TEST REPORT FOR HYDAWAY HYDRAULICS, INC.

Report No.: R9063.01-120-32 R0

Date: 01/13/25

SECTION 11


DRAWINGS

The "As-Built" drawings for the 10' X 10' HydAway Door dated December 20, 2024, and HydAway Hurricane Strap Drawing dated November 8, 2024, which follow, have been reviewed by Intertek B&C and are representative of the project reported herein. Project construction was verified by Intertek B&C per the drawings included in this report. Any deviations are documented herein or on the drawings.

Friday, December 20, 2024 4:16:49 PM

B

B



NOTES:
 1. VIEW IS FROM EXTERIOR

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HYDAWAY HYDRAULIC WALLS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HYDAWAY HYDRAULIC WALLS IS PROHIBITED.



		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN INCHES	DRAWN		
		TOLERANCES:	CHECKED		
		FRACTIONAL ±	ENG APPR.		
		ANGULAR: MACH ± BEND ±	MFG APPR.		
		TWO PLACE DECIMAL ±	Q.A.		
		THREE PLACE DECIMAL ±	COMMENTS:		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14. 5-2009			
		MATERIAL			
		FINISH			
NEXT ASSY	USED ON				
APPLICATION		DO NOT SCALE DRAWING			


Part Number		
TITLE: Small Frame HydAway Test Door		
SIZE	Door Type(s)	REV
A		D
SCALE: 1:30	WEIGHT:	SHEET 1 OF 6

A

A

B

B



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HYDAWAY HYDRAULIC WALLS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HYDAWAY HYDRAULIC WALLS IS PROHIBITED.



		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN INCHES	DRAWN		
		TOLERANCES:	CHECKED		
		FRACTIONAL ±	ENG APPR.		
		ANGULAR: MACH ± BEND ±	MFG APPR.		
		TWO PLACE DECIMAL ±	Q.A.		
		THREE PLACE DECIMAL ±	COMMENTS:		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14. 5-2009			
		MATERIAL			
		FINISH			
NEXT ASSY	USED ON				
APPLICATION		DO NOT SCALE DRAWING			

Part Number		
TITLE: Small Frame HydAway Test Door		
SIZE	Door Type(s)	REV
A		D
SCALE: 1:8	WEIGHT:	SHEET 2 OF 6

A

A


2

1

Friday, December 20, 2024 4:16:49 PM

B

B



SECTION C-C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HYDAWAY HYDRAULIC WALLS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HYDAWAY HYDRAULIC WALLS IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:	NAME	DATE	Part Number
		DIMENSIONS ARE IN INCHES	DRAWN		TITLE: Small Frame HydAway Test Door
		TOLERANCES:	CHECKED		
		FRACTIONAL \pm	ENG APPR.		
		ANGULAR: MACH \pm BEND \pm	MFG APPR.		
		TWO PLACE DECIMAL \pm	Q.A.		
		THREE PLACE DECIMAL \pm	COMMENTS:		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14. 5-2009			
		MATERIAL			SIZE Door Type(s) REV D
	NEXT ASSY	USED ON			
		FINISH			
	APPLICATION	DO NOT SCALE DRAWING			SCALE: 1:5 WEIGHT: SHEET 3 OF 6



2

1





A

A

Friday, December 20, 2024 4:16:49 PM

B

B



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HYDAWAY HYDRAULIC WALLS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HYDAWAY HYDRAULIC WALLS IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES	
TOLERANCES:	
FRACTIONAL: ±	
ANGULAR: MACH ± BEND ±	
TWO PLACE DECIMAL ±	
THREE PLACE DECIMAL ±	
INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14. 5-2009	
MATERIAL	
FINISH	
NEXT ASSY	USED ON
APPLICATION	

DRAWN	NAME	DATE
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		

Part Number		
TITLE: Small Frame HydAway Test Door		
SIZE	Door Type(s)	REV
A		D
SCALE: 1:32		WEIGHT:
		SHEET 4 OF 6



A


A

2

1

Friday, December 20, 2024 4:16:49 PM

Typical Glazing Detail



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HYDAWAY HYDRAULIC WALLS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HYDAWAY HYDRAULIC WALLS IS PROHIBITED.



		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN INCHES	DRAWN		
		TOLERANCES:	CHECKED		
		FRACTIONAL ±	ENG APPR.		
		ANGULAR: MACH ± BEND ±	MFG APPR.		
		TWO PLACE DECIMAL ±	Q.A.		
		THREE PLACE DECIMAL ±	COMMENTS:		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14. 5-2009			
		MATERIAL			
		FINISH			
NEXT ASSY	USED ON				
APPLICATION		DO NOT SCALE DRAWING			

Part Number		
TITLE: Small Frame HydAway Test Door		
SIZE	Door Type(s)	REV
A		D
SCALE: 1:4	WEIGHT:	SHEET 5 OF 6

2

1

2


1

Friday, December 20, 2024 4:16:49 PM

DETAIL FOR THERMAL MODELING OF FOAM GLASS SPACER

B

B



A

A

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HYDAWAY HYDRAULIC WALLS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HYDAWAY HYDRAULIC WALLS IS PROHIBITED.



		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN INCHES	DRAWN		
		TOLERANCES:	CHECKED		
		FRACTIONAL ±	ENG APPR.		
		ANGULAR: MACH ± BEND ±	MFG APPR.		
		TWO PLACE DECIMAL ±	Q.A.		
		THREE PLACE DECIMAL ±	COMMENTS:		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14. 5-2009			
		MATERIAL			
		FINISH			
NEXT ASSY	USED ON				
APPLICATION		DO NOT SCALE DRAWING			

Part Number		
TITLE: Small Frame HydAway Test Door		
SIZE A	Door Type(s)	REV D
SCALE: 2:1	WEIGHT:	SHEET 6 OF 6

2

1

2


1

Friday, November 8, 2024 1:56:17 PM

DOOR CLOSED


B

B




SECTION A-A

1/2"-13 Shoulder Screw



DETAIL B
SCALE 1 : 3



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HYDAWAY HYDRAULIC WALLS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HYDAWAY HYDRAULIC WALLS IS PROHIBITED.



		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	Part Number
		DIMENSIONS ARE IN INCHES		DRAWN		TITLE: Hydaway Hurricane Strap Drawings
		TOLERANCES:		CHECKED		
		FRACTIONAL ±		ENG APPR.		
		ANGULAR: MACH ± BEND ±		MFG APPR.		
		TWO PLACE DECIMAL ±		Q.A.		
		THREE PLACE DECIMAL ±		COMMENTS:		SIZE Door Type(s) REV A
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14. 5-2009				SCALE: 1:75 WEIGHT: SHEET 1 OF 2
		MATERIAL				
		FINISH				
	NEXT ASSY	USED ON				
	APPLICATION		DO NOT SCALE DRAWING			

2

1

A

A

2




1

Friday, November 8, 2024 1:56:17 PM

DOOR OPEN

B

B



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HYDAWAY HYDRAULIC WALLS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HYDAWAY HYDRAULIC WALLS IS PROHIBITED.



UNLESS OTHERWISE SPECIFIED:		NAME	DATE	Part Number
DIMENSIONS ARE IN INCHES		DRAWN		TITLE: Hydaway Hurricane Strap Drawings
TOLERANCES:		CHECKED		
FRACTIONAL ±		ENG APPR.		
ANGULAR: MACH ± BEND ±		MFG APPR.		
TWO PLACE DECIMAL ±		Q.A.		
THREE PLACE DECIMAL ±		COMMENTS:		
INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14. 5-2009				
MATERIAL				SIZE Door Type(s) REV A A
NEXT ASSY	USED ON			SCALE: 1:75 WEIGHT: SHEET 2 OF 2
APPLICATION		DO NOT SCALE DRAWING		

A

A

2

1